

Radiation Protection and Metric Control in the Holographic AU Drive

Yashchenko Dmitry Eduardovich
Ященко Дмитрий Эдуардович
Svobodnyy, Amur Region, Russian Federation
Российская Федерация Амурская область г.
Свободный
yashchenko.dmitry@gmail.com
mi@liberurban.ru
X: @graviton2011
@dmitryactauniversi.bsky.social
<https://boosty.to/actauniversi>
<https://www.patreon.com/c/ACTAUNIVERSI>
<https://sciencaimo.space/>

15.08.2026

In the **Acta Universi (AU)** hypothesis, metric control through the entropy gradient ∇S_Θ opens fundamentally new possibilities not only for movement and artificial gravity, but also for **active radiation protection**. Instead of passive shielding (lead, hydrogen-containing materials, magnetic fields), the AU drive allows the creation of **local spacetime deformations** that deflect, focus, or scatter fluxes of charged particles and high-energy photons, effectively making the spacecraft "invisible" to radiation.

1. Physical Principle: Radiation as a Particle Flux in a Curved Metric

In ordinary flat space, radiation (cosmic rays, solar wind, gamma quanta) travels in straight lines. In the presence of an entropy gradient ∇S_Θ , the effective metric is modified:

$$g_{\mu\nu} = \eta_{\mu\nu} + \beta \partial_\mu S_\Theta \partial_\nu S_\Theta,$$

which is equivalent to the appearance of an **effective refractive index** for all particles (including massless ones):

$$n_{\text{eff}} = 1 - \frac{\lambda}{2r} \frac{dS_\Theta}{dr}.$$

Thus, the particle trajectory bends in the same way light bends in a gradient medium. For a relativistic particle with charge q and mass m , the equation of motion in such a metric is:

$$\frac{d^2 x^\mu}{d\tau^2} + \Gamma_{\nu\rho}^\mu \frac{dx^\nu}{d\tau} \frac{dx^\rho}{d\tau} = \frac{q}{m} F_\nu^\mu \frac{dx^\nu}{d\tau},$$

where $\Gamma_{\nu\rho}^\mu$ are the Christoffel symbols computed from the effective metric. The additional term related to ∇S_Θ creates a **potential barrier** for particles:

$$U_{\text{eff}}(r) = \frac{\lambda c^2}{2} S_\Theta(r) + \frac{L^2}{2mr^2} + \frac{q\phi(r)}{c},$$

where L is the angular momentum and $\phi(r)$ is the electrostatic potential (if present). With a sufficiently large gradient $\frac{dS_\Theta}{dr}$, the potential barrier becomes impenetrable for particles with energy below a certain threshold.

2. Creating an "Entropic Shield"

To protect the spacecraft from radiation, it is sufficient to create a **spherically symmetric gradient** ∇S_Θ around the hull, which will act as a **deflecting lens** or **mirror** for charged particles. The required gradient is estimated from the condition that the Larmor radius (or effective curvature radius) becomes smaller than the transverse size of the spacecraft.

For a proton with energy $E \sim 1$ GeV (typical galactic cosmic rays), the curvature radius in the gradient field is:

$$R_{\text{curv}} \sim \frac{E}{c |\nabla S_\Theta| \cdot \lambda}.$$

To make R_{curv} smaller than the spacecraft radius ($R_{\text{ship}} \sim 10$ m), we require:

$$|\nabla S_\Theta| \gg \frac{E}{c \lambda R_{\text{ship}}} \approx \frac{1.6 \times 10^{-10} \text{ J}}{3 \times 10^8 \cdot 3.8 \times 10^{-12} \cdot 10} \approx 1.4 \times 10^{-8} \text{ bit}/(\text{s} \cdot \text{m}^3).$$

This value is **5 orders of magnitude greater** than that for 1g (2.87×10^{-13}), but still **achievable** with AU chips in active mode (Jump or Boost). For gamma radiation (photons), deflection occurs due to changes in the refractive index, creating a "gravitational lensing" effect that scatters the flux.

3. Real-Time Metric Control

The metric control system (through the activities of the 27 operators) can **adaptively change** the gradient ∇S_Θ depending on the radiation level:

- **In normal mode (1g)** — the gradient is minimal, and radiation protection is practically absent (except for residual effects on the lowest-energy particles).
- **When radiation levels increase** (e.g., during passage through the Van Allen belts, solar flares) — the system automatically increases NNI operator activities, creating a temporary "shield" with $|\nabla S_\Theta| \sim 10^{-8} \text{ bit}/(\text{s}\cdot\text{m}^3)$. This deflects the majority of charged particles.
- **In Boost mode** — the gradient can be even higher ($10^{-6} \text{ bit}/(\text{s}\cdot\text{m}^3)$), providing almost complete protection even from the most energetic cosmic rays.

Energy costs: Creating such a gradient requires a short-term increase in chip power (up to 10–20% of peak), comparable to jump mode.

4. Additional Effects

- **Radiation focusing:** Instead of scattering, radiation fluxes can be focused into safe directions (e.g., away from living modules) using an asymmetric gradient.
 - **Energy absorption:** Part of the radiation energy can be converted into an increase in S_Θ (entropy increases), which theoretically allows radiation to be used as an **additional power source** for the AU field (an "entropic feeding" effect). However, this mechanism has not yet been developed at the engineering level.
 - **Micrometeoroid protection:** High-velocity dust particles are also deflected by the gradient, since their trajectory curves in the effective metric (although the effect is weaker for massive objects than for charged particles).
-

5. Safety and Limitations

- **Feedback:** When creating a high gradient, it is necessary to monitor $\Delta S_\Theta / S_{\Theta,0}$ to avoid exceeding the entropy threshold. However, radiation protection requires a ΔS_Θ much smaller than for a jump, so the risk of a cascade is minimal.
 - **Duration:** The shield can be maintained continuously for several hours, but during prolonged solar flares, switching to passive methods (e.g., reorienting the spacecraft or taking shelter in the shadow of planets) may be necessary.
-

6. Mathematical Summary

Mode	∇S_Θ	(bit/(s·m ³))	Radiation Protection
:---	:---	:---	
Standby	0	None	
1g	10^{-13}	Minimal (only for < 10 keV)	
Jump (10 ly)	10^{28}	(short-term)	Complete, but only during the jump
Shield mode	10^{-8}	Deflects protons up to 100 GeV	
Boost	10^{-6}	Deflects protons up to 10 TeV	

7. Conclusion

In the AU hypothesis, radiation protection and metric control are realized through a **single mechanism** — the creation of a controlled entropy gradient ∇S_Θ . This allows:

- deflecting charged particles without massive shielding,
- adaptively changing the protection level in real time,
- using radiation energy to power the AU field (in the future).

This approach makes the spacecraft not only a transport vehicle but also an **active protection system**, where spacetime itself serves as a shield. This radically reduces the mass and cost of missions, opening the path to long-term interstellar travel.